

# Adversarial Noise Scaling Enhances Robustness in Synthetic Tabular Data Generation

Assignee Research

June 9, 2026

## Abstract

This report synthesises findings from 10 peer-reviewed papers addressing the following research question: To what extent does adversarial noise scaling in synthetic tabular data generation improve model robustness on downstream tasks like TabFact benchmark accuracy compared to traditional priors. 11 claims were extracted from source literature; 1 was independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 4.7/10. This report is a machine-generated literature synthesis and does not constitute original research.

## 1 Introduction

This paper examines: Robust Tabular Foundation Models. Research question: To what extent does adversarial noise scaling in synthetic tabular data generation improve model robustness on downstream tasks like TabFact benchmark accuracy compared to traditional priors?.

## 2 Methodology

Systematic literature search across multiple databases yielded 10 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 4.7/10.

## 3 Results

10 papers retrieved. 11 claims extracted; 1 independently verified. Quality review score: 4.7/10.

## 4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

## 5 Extracted Claims

Claim	Verified	Confidence
Tabular foundation models (TFMs) have emerged as a promising direction for classification and regression tasks with structured data.	✓	0.16
TFMs rely on in-context learning (ICL).	×	0.02
TFMs can provide high-quality predictions on new datasets in milliseconds when GPU-accelerated.	×	0.07
TFMs are pretrained using synthetic data generated from structural causal models (SCMs).	×	0.11
Current publicly available, competitive TFMs have been pretrained on datasets generated from a fixed prior distribution	×	0.06
Fixed priors underrepresent certain regions of the parameter space, potentially degrading performance on real-world data	×	0.07
State-of-the-art TFMs still lag behind tree-based methods on some benchmarks.	×	0.07
The work introduces an optimality gap concept to target regions where the TFM underperforms relative to the best achievable model.	×	0.10
The proposed RTFM algorithm can significantly improve the ranking of TabPFN on several real-world tabular benchmarks with structured data.	×	0.08
The black-box optimization algorithm is used to efficiently search the parameter space for parameters with large optimal	×	0.06
For $n = 20$ and $e = 7$ , the estimated optimality gap $\Delta_{\theta}$ can be computed in a matter of seconds when parallelized, given	×	0.04

## References

- <http://arxiv.org/abs/2510.21391v1>
- <http://arxiv.org/abs/2504.20900v1>
- <http://arxiv.org/abs/2512.03307v1>