

Scaling Properties of Projection-Based Cross-Lingual NER with Target Data Size

Assignee Research

June 24, 2026

Abstract

Cross-lingual Named Entity Recognition (NER) leverages knowledge transfer between languages to identify and classify named entities, making it particularly useful for low-resource languages. We show that the data-based cross-lingual transfer method is an effective technique for crosslingual NER and can outperform multilingual language models for low-resource languages. This paper introduces two key enhancements to the annotation projection step in cross-lingual NER for low-resource languages. First, we explore refining word alignments using back-translation to improve accuracy. Second, we pres

1 Introduction

This paper examines: Revisiting Projection-based Data Transfer for Cross-Lingual Named Entity Recognition in Low-Resource Languages. Research question: What are the scaling properties of projection-based data transfer methods for cross-lingual NER as the size of the target language’s labeled dataset increases, measured by F1-score improvements on the CoNLL-2003 benchmark?.

2 Methodology

Systematic literature search across multiple databases yielded 11 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 7.4/10.

3 Results

11 papers retrieved. 18 claims extracted; 13 independently verified. Quality review score: 7.4/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
The evaluation was performed across a total of 57 languages using the XTREME (39 languages) and MasakhaNER2 datasets (18	✓	0.16
The heuristic word-to-word alignment-based approach was reimplemented according to Garca-Ferrero et al. (2022) and enh	✓	0.26
The EasyProject method uses back-translation of labelled source sentences with the NLLB-200-3.3B2 model for annotation p	✓	0.21
The NLLB200-3.3B3 model was employed as a translation model for all experiments.	×	0.13
The XLM-R-Large model, fine-tuned on the English split of the CONLL2003, served as both the source model and for target	✓	0.18
MISC entities predicted by the XLM-R-Large model were ignored in the first set of experiments.	✓	0.16
SimAlign and non-finetuned AWESoME neural aligners with default settings were used for computing word-to-word alignments	×	0.14
All models were sourced from the HF Hub.	×	0.07
The evaluation metrics were influenced by both translation quality and the performance of the NER models.	×	0.13
The proposed approach involving n-gram candidates extraction provides comparable or superior results while offering grea	✓	0.22
The NER model-based extraction (N) method was used in the experiments.	×	0.09
Projection-based data transfer can outperform multilingual language models for low-resource languages.	✓	0.30
The paper introduces two key enhancements to the annotation projection step in cross-lingual NER for low-resource langua	✓	0.38
The first enhancement explores refining word alignments using back-translation to improve accuracy.	✓	0.20
The second enhancement presents a novel formalized projection approach of matching source entities with extracted target	✓	0.22
The findings highlight the robustness of projection-based data transfer as an alternative to model-based methods for cro	✓	0.44
Data-based methods automate labelling through translation and annotation projection processes while leveraging advanceme	✓	0.31
Translate-test labels original sentences in zero-shot settings, and translate-train generates labelled data to train a N	✓	0.32

References

- <http://arxiv.org/abs/1908.10261v1>
- <http://arxiv.org/abs/2303.09306v2>
- <http://arxiv.org/abs/2501.18750v1>