

# Task Similarity and Zero-Shot Cross-Lingual Transfer Performance in Multilingual Models

Assignee Research

June 23, 2026

## Abstract

In zero-shot cross-lingual transfer, a supervised NLP task trained on a corpus in one language is directly applicable to another language without any additional training. A source of cross-lingual transfer can be as straightforward as lexical overlap between languages (e.g., use of the same scripts, shared subwords) that naturally forces text embeddings to occupy a similar representation space. Recently introduced cross-lingual language model (XLM) pretraining brings out neural parameter sharing in Transformer-style networks as the most important factor for the transfer. In this paper, we aim

## 1 Introduction

This paper examines: Analyzing Zero-shot Cross-lingual Transfer in Supervised NLP Tasks. Research question: Does task similarity measured via taxonomy or embeddings correlate with zero-shot performance gains in cross-lingual transfer when using multilingual models like mT5 or XLM-R?.

## 2 Methodology

Systematic literature search across multiple databases yielded 13 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 7.3/10.

## 3 Results

13 papers retrieved. 10 claims extracted; 8 independently verified. Quality review score: 7.3/10.

## 4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

## 5 Extracted Claims

Claim	Verified	Confidence
XLM by Conneau & Lample was pretrained using only masked language modeling (MLM).	✓	0.19
XLM has reported state-of-the-art performance on downstream cross-lingual language understanding benchmarks.	×	0.14
Recent studies indicate that parameter sharing induced by the Transformer architecture is the most attributable factor f	✓	0.22
XLM-RoBERTa (XLM-R) outputs token embeddings consisting of up to 512 token vectors of 768 dimensions each for a given in	✓	0.16
The study adopts a Siamese network architecture by Sentence-BERT to avoid combinatorial explosion when forming sentence	✓	0.16
The dataset used consists of sentence pairs from image captions, news headlines, and user forums.	✓	0.19
The dataset is partitioned into a training set of 5,749 pairs, a development set of 1,500 pairs, and a test set of 1,379	×	0.10
STSb sentence pairs are labeled with a similarity score ranging from 0 to 5.	✓	0.21
The study evaluates cross-lingual transfer on Semantic Textual Similarity (STS), Machine Reading Comprehension (MRC/SQuA	✓	0.19
The proposed method computes a projection matrix to directly map sentence embeddings of one language to those of another	✓	0.15

## References

- <http://arxiv.org/abs/2210.09934v1>

- <http://arxiv.org/abs/2101.10649v1>
- <http://arxiv.org/abs/2310.09917v3>