

# Synthetic-to-Real Data Ratios in Pretraining for Cross-Domain Tabular Foundation Models

Assignee Research

June 9, 2026

## Abstract

This report synthesises findings from 4 peer-reviewed papers addressing the following research question: How does varying the ratio of synthetic to real data in pretraining affect the cross-domain generalization accuracy of tabular foundation models on healthcare and finance benchmarks. 12 claims were extracted from source literature; 1 was independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 4.5/10. This report is a machine-generated literature synthesis and does not constitute original research.

## 1 Introduction

This paper examines: Robust Tabular Foundation Models. Research question: How does varying the ratio of synthetic to real data in pretraining affect the cross-domain generalization accuracy of tabular foundation models on healthcare and finance benchmarks?.

## 2 Methodology

Systematic literature search across multiple databases yielded 4 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 4.5/10.

## 3 Results

4 papers retrieved. 12 claims extracted; 1 independently verified. Quality review score: 4.5/10.

## 4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

## 5 Extracted Claims

Claim	Verified	Confidence
Tabular foundation models (TFMs) rely on in-context learning (ICL) for classification and regression tasks with structured	×	0.11
TFMs can produce high-quality predictions on new datasets in milliseconds when GPU-accelerated.	×	0.07
Training TFMs relies on generating diverse synthetic datasets constructed from structural causal models (SCMs).	×	0.08
All current publicly available, competitive TFMs have been pretrained on datasets generated from a fixed prior distribution	×	0.06
Fixed priors in TFM training underrepresent certain regions of the parameter space, potentially degrading performance on	×	0.06
State-of-the-art TFMs lag behind tree-based methods on some benchmarks.	×	0.06
The proposed method formalizes adversarial training over the SCM parameter space to adapt to challenging regions such as	×	0.06
The proposed algorithm is named ROBUST TABULAR FOUNDATION MODELS (RTFM).	✓	0.18
Applying RTFM to TabPFN V2 using only 90k additional training datasets significantly improves its ranking on several rea	×	0.12
The maximization stage of the proposed algorithm uses a black-box optimization algorithm to search the parameter space f	×	0.01
In the described implementation, the estimated optimality gap could be computed in a matter of seconds when parallelized	×	0.04
The implementation used ncores equal to the product of nds (number of sampled generators) and e (number of baseline esti	×	0.03

## References

- <http://arxiv.org/abs/2310.18430v3>
- <http://arxiv.org/abs/2507.07829v1>

- <http://arxiv.org/abs/2512.03307v1>