

Top-Related Meta-Learning for Semantic Bias Reduction in Few-Shot Object Detection

Assignee Research

June 7, 2026

Abstract

This report synthesises findings from 5 peer-reviewed papers addressing the following research question: Does the Top-Related Meta-Learning approach reduce semantic bias in few-shot object detection when evaluated on imbalanced subsets of the COCO benchmark. 6 claims were extracted from source literature; 3 were independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 6.5/10. This report is a machine-generated literature synthesis and does not constitute original research.

1 Introduction

This paper examines: Top-Related Meta-Learning Method for Few-Shot Object Detection. Research question: Does the Top-Related Meta-Learning approach reduce semantic bias in few-shot object detection when evaluated on imbalanced subsets of the COCO benchmark?.

2 Methodology

Systematic literature search across multiple databases yielded 5 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 6.5/10.

3 Results

5 papers retrieved. 6 claims extracted; 3 independently verified. Quality review score: 6.5/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
The proposed method significantly outperforms previous state-of-the-art methods for few-shot detection.	×	0.10
The proposed method improves detection APs by almost 4% for few-shot detection compared with previous competitive baseli	×	0.10
The proposed method splits all categories into disjoint groups to improve detection performance without additional sub-m	✓	0.18
The proposed method captures the correlation between groups or categories from the category-based meta-features to reduc	✓	0.16
The proposed method uses TCL-C for classification and category-based grouping mechanism to help meta-model M learn the r	✓	0.26
The input of the meta-model M is an image and a mask of only an object selected randomly.	×	0.06

References

- <http://arxiv.org/abs/2507.20019v1>
- <http://arxiv.org/abs/2003.04390v4>
- <http://arxiv.org/abs/2007.06837v6>