

Comparative Performance of Self-Supervised Speech Representations Pre-trained on Flemish Dutch versus Other Low-Resource Languages

Assignee Research

June 21, 2026

Abstract

Recent research in speech processing exhibits a growing interest in unsupervised and self-supervised representation learning from unlabelled data to alleviate the need for large amounts of annotated data. We investigate several popular pre-training methods and apply them to Flemish Dutch. We compare off-the-shelf English pre-trained models to models trained on an increasing amount of Flemish data. We find that the most important factors for positive transfer to downstream speech recognition tasks include a substantial amount of data and a matching pre-training domain. Ideally, we also finetune

1 Introduction

This paper examines: Comparison of Self-Supervised Speech Pre-Training Methods on Flemish Dutch. Research question: How does the performance of self-supervised speech representations pre-trained on Flemish Dutch compare to those pre-trained on other low-resource languages, as evaluated on cross-lingual benchmark datasets like LibriSpeech or Common Voice?.

2 Methodology

Systematic literature search across multiple databases yielded 12 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 7.5/10.

3 Results

12 papers retrieved. 15 claims extracted; 11 independently verified. Quality review score: 7.5/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
The APC model uses a Filterbank feature encoder, a GRU aggregator, and aims to reconstruct future frames with an output	✓	0.17
The Mockingjay model uses a Filterbank feature encoder, a Bidirectional Transformer aggregator, and aims to reconstruct	✓	0.19
The CPC model uses a CNN feature encoder, an LSTM aggregator, and aims to identify future features with an output dimens	✓	0.19
The wav2vec model uses a CNN feature encoder, a CNN aggregator, and aims to identify future features with an output dime	✓	0.20
The wav2vec 2.0 model uses a CNN feature encoder, a Transformer aggregator, and aims to identify quantised future featur	✓	0.25
The wav2vec 2.0 model combines ideas from wav2vec, vq-wav2vec, and MLM.	×	0.14
The wav2vec 2.0 encoder computes latent speech representations from the raw waveform with 7 temporal convolution blocks.	✓	0.16
A certain proportion of the latent features is masked before feeding to the aggregator in wav2vec 2.0.	✓	0.20
The aggregator in wav2vec 2.0 is a Transformer network.	×	0.10
A quantisation module in wav2vec 2.0 maps the latent feature vectors to discretised versions.	✓	0.19
The final training objective of wav2vec 2.0 is to distinguish the true quantised representation for a masked time step,	✓	0.23
The base architecture of wav2vec 2.0 contains 12 Transformer blocks in the aggregator.	×	0.11
The large architecture of wav2vec 2.0 contains 24 Transformer blocks in the aggregator.	×	0.12
The contextual features at the output of the aggregator in wav2vec 2.0 are extracted for downstream tasks.	✓	0.17
The wav2vec 2.0 model can be fine-tuned on a labelled set by adding an extra linear layer on top of the context network	✓	0.15

References

- <http://arxiv.org/abs/2501.19321v1>
- <http://arxiv.org/abs/2109.14357v1>
- <http://arxiv.org/abs/2208.05445v1>