

Impact of Semantic Disentanglement Heads on Meta-Learning Detector Convergence and mAP in Low-Data Regimes

Assignee Research

June 11, 2026

Abstract

Many meta-learning methods are proposed for few-shot detection. However, previous most methods have two main problems, poor detection APs, and strong bias because of imbalance and insufficient datasets. Previous works mainly alleviate these issues by additional datasets, multi-relation attention mechanisms and sub-modules. However, they require more cost. In this work, for meta-learning, we find that the main challenges focus on related or irrelevant semantic features between categories. Therefore, based on semantic features, we propose a Top-C classification loss (i.e., TCL-C) for classificat

1 Introduction

This paper examines: Top-Related Meta-Learning Method for Few-Shot Object Detection. Research question: What is the impact of replacing multi-relation attention modules with semantic disentanglement heads on the convergence speed and final mAP of meta-learning detectors in low-data regimes?.

2 Methodology

Systematic literature search across multiple databases yielded 13 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 7.6/10.

3 Results

13 papers retrieved. 6 claims extracted; 5 independently verified. Quality review score: 7.6/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
The proposed method significantly outperforms previous state-of-the-art methods for few-shot detection.	✓	0.17
The proposed method improves detection APs by almost 4% for few-shot detection compared with previous competitive baseli	×	0.15
The proposed method splits all categories into disjoint groups to improve detection performance without additional sub-m	✓	0.20
The proposed method captures the correlation between groups or categories from the category-based meta-features to reduc	✓	0.23
The proposed method uses TCL-C for classification and category-based grouping mechanism to help meta-model M learn the r	✓	0.24
The input of the meta-model M is an image and a mask of only an object selected randomly.	✓	0.25

References

- <http://arxiv.org/abs/2210.13923v1>
- <http://arxiv.org/abs/2203.07057v2>
- <http://arxiv.org/abs/2007.06837v6>