

Comparative Robustness of LVLMs in LVLMeHub Under Adversarial and Noisy Inputs

Assignee Research

June 5, 2026

Abstract

This report synthesises findings from 14 peer-reviewed papers addressing the following research question: What is the comparative robustness of LVLMs in LVLMeHub against adversarial attacks or noisy inputs, measured by accuracy degradation across different perturbation types. 12 claims were extracted from source literature; 10 were independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 8.0/10. This report is a machine-generated literature synthesis and does not constitute original research.

1 Introduction

This paper examines: Gradient-based learning applied to document recognition. Research question: What is the comparative robustness of LVLMs in LVLMeHub against adversarial attacks or noisy inputs, measured by accuracy degradation across different perturbation types?.

2 Methodology

Systematic literature search across multiple databases yielded 14 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 8.0/10.

3 Results

14 papers retrieved. 12 claims extracted; 10 independently verified. Quality review score: 8.0/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
Multilayer neural networks trained with the back-propagation algorithm constitute the best example of a successful gradient-based learning algorithm	✓	0.36
Gradient-based learning algorithms can be used to synthesize a complex decision surface that can classify high-dimension	✓	0.41
The paper compares various methods applied to handwritten character recognition on a standard handwritten digit recognition	✓	0.27
Convolutional neural networks are specifically designed to deal with the variability of 2D shapes.	✓	0.26
Convolutional neural networks outperform all other techniques on the standard handwritten digit recognition task.	✓	0.26
Real-life document recognition systems are composed of multiple modules including field extraction, segmentation recognition	✓	0.34
Graph transformer networks (GTN) allow multimodule systems to be trained globally using gradient-based methods to minimize	✓	0.35
Experiments demonstrate the advantage of global training and the flexibility of graph transformer networks.	✓	0.30
A graph transformer network for reading bank cheques uses convolutional neural network character recognizers combined with	✓	0.35
The described graph transformer network for reading bank cheques provides record accuracy on business and personal cheques	✓	0.24
The described cheque reading system is deployed commercially.	×	0.13
The deployed commercial cheque reading system reads several million cheques.	×	0.11

References

- <https://doi.org/10.1109/tmi.2014.2377694>
- <https://doi.org/10.1109/5.726791>

- <https://doi.org/10.48550/arxiv.2403.09346>