

# Causal Synthetic Data Augmentation vs Adversarial Training for Tabular Foundation Model Robustness

Assignee Research

June 8, 2026

## Abstract

This report synthesises findings from 11 peer-reviewed papers addressing the following research question: How does causal synthetic data augmentation compare to standard adversarial training in improving the cross-domain robustness of tabular foundation models on the TabMNAR benchmark. 16 claims were extracted from source literature; 1 was independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 4.3/10. This report is a machine-generated literature synthesis and does not constitute original research.

## 1 Introduction

This paper examines: Causal Data Augmentation for Robust Fine-Tuning of Tabular Foundation Models. Research question: How does causal synthetic data augmentation compare to standard adversarial training in improving the cross-domain robustness of tabular foundation models on the TabMNAR benchmark?.

## 2 Methodology

Systematic literature search across multiple databases yielded 11 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 4.3/10.

## 3 Results

11 papers retrieved. 16 claims extracted; 1 independently verified. Quality review score: 4.3/10.

## 4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.



## 5 Extracted Claims

| Claim   | Verified | Confidence |
|---|----------|------------|
| Experiments were conducted on the Mitra model across 33 classification datasets with 10 folds each from the TabArena ben  | ×        | 0.07       |
| The study totaled 2,310 fine-tuning runs.   | ×        | 0.12       |
| Model performance is reported as normalized ROC-AUC relative to the pre-trained model.  | ×        | 0.08       |
| CausalMixFT achieves a median improvement of $+0.12 \pm 0.63$ over the pre-trained model.   | ×        | 0.05       |
| The default fine-tuning baseline achieves a median improvement of $+0.10 \pm 0.98$ over the pre-trained model.  | ×        | 0.08       |
| Purely synthetic augmentation methods (CTGAN, SCM, TabEBM, TableAugment, and MixedModel) show negative median improvement   | ×        | 0.08       |
| CausalMixFT has a performance variability of $\pm 0.63$ , while default fine-tuning has a variability of $\pm 0.98$ .   | ×        | 0.09       |
| In average rank analysis across datasets, CausalMixFT ranks first overall.  | ×        | 0.03       |
| In average rank analysis, the default fine-tuning baseline ranks second, followed by purely synthetic generators.   | ×        | 0.08       |
| The normalization strategy uses the base model’s (Mitra’s) zero-shot performance as the baseline.   | ×        | 0.03       |
| The normalization formula is defined as: $\text{score\_normalized} = \text{metric\_sign} \times (\text{score\_method} / \text{score\_baseline} - 1) \times 100\%$ . | ×        | 0.00       |
| The method generates synthetic data using Structural Causal Models (SCMs) fitted to the target dataset.   | ✓        | 0.22       |
| Structural relations between features are estimated using the PC and FCI algorithms.  | ×        | 0.03       |
| The estimation process produces a probabilistic adjacency matrix encoding edge strengths between variables.   | ×        | 0.03       |
| DAGs are sampled and fitted using DoWhy’s SCM framework with additive noise models.   | ×        | 0.03       |
| Numerical features are modeled with regressors and categorical features with classifiers within the SCM.  | ×        | 0.05       |

## References

- <http://arxiv.org/abs/2601.04110v2>
- <http://arxiv.org/abs/2407.21523v1>
- <http://arxiv.org/abs/2512.03307v1>