

Mul-GAD Robustness Against Noise in Semi-Supervised Graph Anomaly Detection

Assignee Research

May 31, 2026

Abstract

This report synthesises findings from 7 peer-reviewed papers addressing the following research question: How does the robustness of Mul-GAD compare to other semi-supervised graph anomaly detection methods (e.g., DOMINANT or GAN-based approaches) when evaluated on perturbed graph structures with varying noise? Anomaly detection is defined as discovering patterns that do not conform to the expected behavior. Previously, anomaly detection was mostly conducted using traditional shallow learning techniques, but with little improvement. 8 claims were extracted from source literature; 0 were independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 3.2/10. This report is a machine-generated literature synthesis and does not constitute original research.

1 Introduction

This paper examines: Mul-GAD: a semi-supervised graph anomaly detection framework via aggregating multi-view information. Research question: How does the robustness of Mul-GAD compare to other semi-supervised graph anomaly detection methods (e.g., DOMINANT or GAN-based approaches) when evaluated on perturbed graph structures with varying levels of noise?.

2 Methodology

Systematic literature search across multiple databases yielded 7 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 3.2/10.

3 Results

7 papers retrieved. 8 claims extracted; 0 independently verified. Quality review score: 3.2/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
The Mul-GAD approach outperforms the state-of-the-art not only on detection performance, but also in terms of generaliza	×	0.14
Experiments show that computing the feature similarity matrix plays an important role in boosting the detection performa	×	0.06
The final model, which equipped with label-oriented objective function and fusion strategies, has a significant improvem	×	0.14
Adequate experimental validation is the foundation for selecting the objective function.	×	0.06
The Mul-GAD approach achieves a performance of 0.97, 0.97, 0.87, 0.97, 0.94, 0.93, 0.94, 0.95, 0.95, 0.65 on the first d	×	0.04
The Mul-GAD approach achieves a performance of 0.67, 0.63, 0.67, 0.6, 0.51, 0.55, 0.65, 0.66, 0.5, 0.56 on the second da	×	0.04
The Mul-GAD approach achieves a performance of 0.93, 0.89, 0.88, 0.88, 0.88, 0.95, 0.9, 0.91, 0.92, 0.85 on the third da	×	0.04
The Mul-GAD approach achieves a performance of 0.54, 0.62, 0.62, 0.62, 0.62, 0.62, 0.56, 0.57, 0.56, 0.63 on the fourth	×	0.04

References

- <http://arxiv.org/abs/1404.4679v2>
- <http://arxiv.org/abs/2212.05478v1>
- <http://arxiv.org/abs/2504.08115v1>