

# ReST-KV Throughput Gains Over Attention-Weight Eviction in Long-Sequence Toxicity Classification

Assignee Research

June 7, 2026

## Abstract

This report synthesises findings from 9 peer-reviewed papers addressing the following research question: What is the throughput improvement of ReST-KV compared to attention-weight eviction methods in long-sequence toxicity classification tasks on ToxicBench when using 7B and 13B models. 15 claims were extracted from source literature; 0 were independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 2.8/10. This report is a machine-generated literature synthesis and does not constitute original research.

## 1 Introduction

This paper examines: ReST-KV: Robust KV Cache Eviction with Layer-wise Output Reconstruction and Spatial-Temporal Smoothing. Research question: What is the throughput improvement of ReST-KV compared to attention-weight eviction methods in long-sequence toxicity classification tasks on ToxicBench when using 7B and 13B models?.

## 2 Methodology

Systematic literature search across multiple databases yielded 9 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 2.8/10.

## 3 Results

9 papers retrieved. 15 claims extracted; 0 independently verified. Quality review score: 2.8/10.

## 4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.



## 5 Extracted Claims

Claim	Verified	Confidence
ReST-KV is evaluated on five open-source LLMs: Llama2-Chat, Gemma-Instruct, Llama3-Instruct, Mistral-Instruct-v0.3, and	×	0.09
ReST-KV is compared with five baseline methods: StreamingLLM, H2O, TOVA, SnapKV, and LaCache.	×	0.04
ReST-KV is evaluated on four benchmarks: LongBench, RULER, Needle-in-a-Haystack, and InniteBench.	×	0.10
ReST-KV achieves the best performance in most cases on the LongBench benchmark.	×	0.06
ReST-KV reduces peak memory usage by approximately 36.0% compared to full cache at a context length of 128k.	×	0.07
ReST-KV achieves an approximate 10.61 $\times$ speedup over the full cache method at a 128K context length.	×	0.10
ReST-KV is compatible with prell sparse attention approaches, yielding a Time-To-First-Token (TTFT) speedup of up to 3.	×	0.04
ReST-KV uses a xed cache budget to limit the number of KV pairs, overcoming the latency bottleneck for long sequences.	×	0.09
ReST-KV only requires computing attention outputs within a small query window, resulting in a computational complexity c	×	0.04
LLMs typically decode text in an auto-regressive manner, which allows them to generate high-quality, contextually cohere	×	0.03
KV cache reduces redundant computation by storing previously computed keys and values.	×	0.06
At each decoding step $t$ , the KV cache stores previously computed keys and values $K_{1:t-1}$ , $V_{1:t-1}$ for $X[1 : t - 1]$ .	×	0.04
The model requires only the current token $x_t$ to generate $x_{t+1}$ , rather than the full sequence $X = [x_1, \dots, x_t]$ .	×	0.02
The query $q_t$ , key $k_t$ , and value $v_t$ are computed as: $q_t = x_t W_Q$ , $k_t = x_t W_K$ , $v_t = x_t W_V$ .	×	0.03
The currently computed $k_t$ and $v_t$ will be concatenated with the previously cached keys and values, and used in the attent	×	0.02

## References

- <http://arxiv.org/abs/2603.21389v1>
- <http://arxiv.org/abs/2508.11281v3>
- <http://arxiv.org/abs/2605.08840v1>