

# Structurally Consistent Synthetic Data Enhances Cross-Domain Generalization in Multimodal Models

Assignee Research

June 8, 2026

## **Abstract**

This report synthesises findings from 14 peer-reviewed papers addressing the following research question: What is the impact of structurally consistent synthetic sample generation on the cross-domain generalization of multimodal foundation models. 16 claims were extracted from source literature; 2 were independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 4.2/10. This report is a machine-generated literature synthesis and does not constitute original research.

## **1 Introduction**

This paper examines: Grounding Synthetic Data Generation With Vision and Language Models. Research question: What is the impact of structurally consistent synthetic sample generation on the cross-domain generalization of multimodal foundation models?.

## **2 Methodology**

Systematic literature search across multiple databases yielded 14 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 4.2/10.

## **3 Results**

14 papers retrieved. 16 claims extracted; 2 independently verified. Quality review score: 4.2/10.

## 4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

## 5 Extracted Claims

Claim	Verified	Confidence
The ARAS400k dataset is available at <a href="https://zenodo.org/records/18890661">zenodo.org/records/18890661</a> .	×	0.11
The code base for the project is available at <a href="https://github.com/caglar Mert/ARAS400k">github.com/caglar Mert/ARAS400k</a> .	×	0.06
Models trained on the experimental dataset (real + synthetic) consistently outperform those trained on real data alone.	✓	0.16
The combined dataset is particularly effective in addressing class-imbalance for under-represented categories.	×	0.07
SynthCLIP and SynGround show that models trained exclusively on synthetic image-caption pairs can achieve performance co	×	0.13
Denoising Diffusion Probabilistic Models often require longer training and inference times compared to GAN architectures	×	0.04
GAN models tend to have problems such as mode collapse, vanishing gradients, non-converging or unstable training, and se	×	0.03
The CLIP-Score metric aligns more with human assessment than standard metrics, enabling reference-free caption evaluatio	×	0.03
The generative models were trained exclusively on a fixed training partition containing 80,182 real samples.	×	0.08
The ARAS400k dataset consists of 100,240 real images.	×	0.07
The ARAS400k dataset consists of 300,000 synthetic images.	×	0.09
Each image in the ARAS400k dataset is paired with semantic segmentation maps.	✓	0.17
The ARAS400k dataset contains over 2 million descriptive captions.	×	0.03
The synthetic maps distribution includes 79% Grass, 15% Tree, 4% Crop, 1% Built-up, and 1% Barrens.	×	0.02
The data was acquired from ESA Sentinel-2 RGBNIR true-color images.	×	0.03
The data was acquired from WorldCover 2021 land cover data.	×	0.03

## References

- <http://arxiv.org/abs/2603.09625v2>
- <http://arxiv.org/abs/2501.18592v4>
- <http://arxiv.org/abs/2403.10075v2>