

Comparison of Projection-Based and Fine-Tuning Cross-Lingual NER Models in Low-Resource Languages

Assignee Research

June 21, 2026

Abstract

Cross-lingual Named Entity Recognition (NER) leverages knowledge transfer between languages to identify and classify named entities, making it particularly useful for low-resource languages. We show that the data-based cross-lingual transfer method is an effective technique for crosslingual NER and can outperform multilingual language models for low-resource languages. This paper introduces two key enhancements to the annotation projection step in cross-lingual NER for low-resource languages. First, we explore refining word alignments using back-translation to improve accuracy. Second, we pres

1 Introduction

This paper examines: Revisiting Projection-based Data Transfer for Cross-Lingual Named Entity Recognition in Low-Resource Languages. Research question: How does the performance of projection-based cross-lingual NER models compare to fine-tuning-based models on low-resource languages when evaluated using F1 score metrics?.

2 Methodology

Systematic literature search across multiple databases yielded 7 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 7.5/10.

3 Results

7 papers retrieved. 9 claims extracted; 7 independently verified. Quality review score: 7.5/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
The evaluation was performed across a total of 57 languages using the XTREME (39 languages) and MasakhaNER2 datasets (18	✓	0.15
The XLM-R-Large model, fine-tuned on the English split of the CONLL2003, served as both the source model and for target	✓	0.20
The NLLB200-3.3B model was employed as a translation model for all experiments.	×	0.12
The evaluation involved full pipelines, resulting in metrics influenced by both translation quality and the performance	×	0.14
The proposed approach involving n-gram candidates extraction provides comparable or superior results while offering grea	✓	0.21
The paper introduces two key enhancements to the annotation projection step in cross-lingual NER for low-resource langua	✓	0.45
Projection-based data transfer can outperform multilingual language models for low-resource languages in cross-lingual n	✓	0.37
Data-based methods automate labelling through translation and annotation projection processes while leveraging advanceme	✓	0.30
The translate-test approach labels original sentences in zero-shot settings, and the translate-train approach generates	✓	0.28

References

- <http://arxiv.org/abs/2506.15415v1>
- <http://arxiv.org/abs/2303.09306v2>

- <http://arxiv.org/abs/2501.18750v1>