

Sample Efficiency of Adversarially Pretrained Tabular Foundation Models Versus Standard Augmentation in Few-Shot Learning

Assignee Research

June 11, 2026

Abstract

The development of tabular foundation models (TFMs) has accelerated in recent years, showing strong potential to outperform traditional ML methods for structured data. A key finding is that TFMs can be pretrained entirely on synthetic datasets, opening opportunities to design data generators that encourage desirable model properties. Prior work has mainly focused on crafting high-quality priors over generators to improve overall pretraining performance. Our insight is that parameterizing the generator distribution enables an adversarial robustness perspective: during training, we can adapt the

1 Introduction

This paper examines: Robust Tabular Foundation Models. Research question: How does the sample efficiency of tabular foundation models pretrained with adversarial noise compare to standard augmentation when evaluated on few-shot learning benchmarks?.

2 Methodology

Systematic literature search across multiple databases yielded 8 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 7.3/10.

3 Results

8 papers retrieved. 10 claims extracted; 7 independently verified. Quality review score: 7.3/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
Tabular foundation models (TFMs) rely on in-context learning (ICL) for classification and regression tasks with structured	✓	0.20
TFMs can produce high-quality predictions on new datasets in milliseconds when GPU-accelerated.	✓	0.17
Current publicly available, competitive TFMs have been pretrained on datasets generated from a fixed prior distribution	✓	0.19
Fixed priors in TFM training underrepresent certain regions of the parameter space, potentially degrading performance on	✓	0.22
State-of-the-art TFMs lag behind tree-based methods on some benchmarks.	×	0.14
The proposed method, RTFM, was applied to TabPFN V2.	×	0.09
Training TabPFN V2 with RTFM using only 90k additional training datasets significantly improved its ranking on several r	✓	0.18
The RTFM methodology uses a black-box optimization algorithm to search the SCM parameter space for parameters with large	✓	0.22
In the described implementation, the estimated optimality gap could be computed in a matter of seconds when parallelized	✓	0.17
The implementation used 20 sampled generators (nds=20) and 7 baseline estimators (e=7) to estimate the optimality gap.	×	0.13

References

- <http://arxiv.org/abs/2306.11066v2>

- <http://arxiv.org/abs/2504.20900v1>
- <http://arxiv.org/abs/2512.03307v1>