

Training Strategies for Language Model Generalization in Mathematical Reasoning

Assignee Research

June 7, 2026

Abstract

This report synthesises findings from 4 peer-reviewed papers addressing the following research question: What training strategies improve language model generalization to novel mathematical reasoning problems v20. 9 claims were extracted from source literature; 0 were independently verified against retrieved documents. An automated multi-reviewer quality assessment produced a score of 3.8/10. This report is a machine-generated literature synthesis and does not constitute original research.

1 Introduction

This paper examines: ARS: Adaptive Reasoning Suppression for Efficient Large Reasoning Language Models. Research question: What training strategies improve language model generalization to novel mathematical reasoning problems v20.

2 Methodology

Systematic literature search across multiple databases yielded 4 papers. Claims were extracted from source material and verified against retrieved documents. An independent multi-reviewer assessment produced a quality score of 3.8/10.

3 Results

4 papers retrieved. 9 claims extracted; 0 independently verified. Quality review score: 3.8/10.

4 Limitations

This report is a machine-generated literature synthesis and does not constitute original research. Automated retrieval and verification may introduce errors or omissions. Review scores reflect automated assessment, not human peer review. Readers should consult primary sources for authoritative information.

5 Extracted Claims

Claim	Verified	Confidence
ARS achieves superior length reduction while maintaining competitive accuracy across all model scales.	×	0.13
ARS operates through three core components: Multi-checkpoint certainty estimation, Progressive threshold adaptation, and	×	0.14
ARS establishes multiple checkpoints at regular intervals during generation.	×	0.02
At each checkpoint, ARS estimates model certainty through tentative answer probing.	×	0.05
The heuristic difficulty estimation is used to schedule the mode of operation in ARS.	×	0.02
ARS uses different policies (CoDFastPolicy, ElasticModeratePolicy, DeepReflectPolicy) based on the difficulty of the que	×	0.02
ARS sets a maximum token limit of 1200 tokens per response.	×	0.02
ARS aims to minimize the expected output length while preserving reasoning accuracy.	×	0.07
ARS uses specific keywords such as 'Wait', 'But', 'Alternatively' to identify reflection behaviors.	×	0.01

References

- <http://arxiv.org/abs/2412.11553v2>
- <http://arxiv.org/abs/2510.00071v2>
- <http://arxiv.org/abs/2510.17496v2>